

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Version 2.0 Revision Date 28.07.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : InstantBlue™

Product Number : ISB1L Brand : Expedeon

REACH No. : A registration number is not available for this substance as the substance

or its uses are exempted from registration, the annual tonnage does not require a registration or the registration is envisaged for a later registration

deadline.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company : Expedeon Ltd.

Unit 12 Buckingway Business Park

Anderson Road CB24 4AE Swavesey Cambridgeshire UNITED KINGDOM

Telephone : +44 (0)1223 873364 Fax : +44 (0)1223 873371 E-mail address : info@expedeon.com

1.4 Emergency telephone number

Emergency Phone # : +44 (0)1223 873364

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Corrosive to metals (Category 1), H290 Skin irritation (Category 2), H315 Eye irritation (Category 2), H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

Classification according to EU Directives 67/548/EEC or 1999/45/EC

Xi Irritant R36/38

For the full text of the R-phrases mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal word Warning

Hazard statement(s)

H290 May be corrosive to metals. H315 Causes skin irritation.

Expedeon - ISB1L Page 1 of 8

H319 Causes serious eye irritation.

Precautionary statement(s)

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Supplemental Hazard

Statements

none

According to European Directive 67/548/EEC as amended.

Hazard symbol(s) Xi Irritant



R-phrase(s)

R36/38 Irritating to eyes and skin.

S-phrase(s)

S26 In case of contact with eyes, rinse immediately with plenty of water and

seek medical advice.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Synonyms : Ultrafast Protein Stain

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component		Classification	Concentration
Phosphoric acid			
CAS-No. EC-No. Index-No.	7664-38-2 231-633-2 015-011-00-6	Met. Corr. 1; Skin Corr. 1B; H290, H314	>= 10 - < 20 %

Hazardous ingredients according to Directive 1999/45/EC

Component		Classification	Concentration
Phosphoric acid			
CAS-No.	7664-38-2	C, R34	>= 10 - < 20 %
EC-No. Index-No.	231-633-2 015-011-00-6		

For the full text of the H-Statements and R-Phrases mentioned in this Section, see Section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Expedeon - ISB1L Page 2 of 8

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation.

Evacuate personnel to safe areas.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid inhalation of vapour or mist.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage temperature 2 - 8 °C

Storage class (TRGS 510): Non-combustible, corrosive hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Expedeon - ISB1L Page 3 of 8

Component	CAS-No.	Value	Control parameters	Basis
Phosphoric acid	7664-38-2	TWA	1 mg/m3	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
	Remarks	Indicative		
		STEL	2 mg/m3	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
		Indicative		
		TWA	1 mg/m3	UK. EH40 WEL - Workplace Exposure Limits
		STEL	2 mg/m3	UK. EH40 WEL - Workplace Exposure Limits
Ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m3	UK. EH40 WEL - Workplace Exposure Limits
		Where no specific short-term exposure limit is listed, a figur times the long-term exposure should be used		

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Colour: brown

b) Odour No data available

Expedeon ISB1L Page 4 of 8

c)	Odour Threshold	No data available		
d)	рН	No data available		
e)	Melting point/freezing point	No data available		
f)	Initial boiling point and boiling range	No data available		
g)	Flash point	No data available		
h)	Evaporation rate	No data available		
i)	Flammability (solid, gas)	No data available		
j)	Upper/lower flammability or explosive limits	No data available		
k)	Vapour pressure	No data available		
I)	Vapour density	No data available		
m)	Relative density	No data available		
n)	Water solubility	No data available		
o)	Partition coefficient: n- octanol/water	No data available		
p)	Auto-ignition temperature	No data available		
q)	Decomposition temperature	No data available		
r)	Viscosity	No data available		
s)	Explosive properties	No data available		
t)	Oxidizing properties	No data available		
Other safety information				

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Organic materials, Powdered metals

10.6 Hazardous decomposition products

Other decomposition products - No data available In the event of fire: see section 5

Expedeon ISB1L Page 5 of 8

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

Expedeon ISB1L Page 6 of 8

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1805 IMDG: 1805 IATA: 1805

14.2 UN proper shipping name

ADR/RID: PHOSPHORIC ACID SOLUTION IMDG: PHOSPHORIC ACID SOLUTION

IATA: Phosphoric acid, solution

14.3 Transport hazard class(es)

ADR/RID: 8 IMDG: 8 IATA: 8

14.4 Packaging group

ADR/RID: III IMDG: III IATA: III

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

14.6 Special precautions for user

No data available

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No data available

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation. H319 Causes serious eye irritation.

Met. Corr. Corrosive to metals Skin Corr. Skin corrosion

Full text of R-phrases referred to under sections 2 and 3

C Corrosive R34 Causes burns.

R36/38 Irritating to eyes and skin.

Expedeon ISB1L Page 7 of 8

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Expedeon and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.expedeon.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Expedeon ISB1L Page 8 of 8